



平行管螺纹阴接头




型号	适用管外径 øA	T	øB	øC	D	对边宽		L1	L2
						E	F		
8FKCO06010	6	G1/8	4	17	17.5	14	14	6	32.5
8FKCO08010	8		4	17	17.5	17	17	6	32.5
8FKCO08020	8	G1/4	6	20.5	17.5	19	17	10	33.5
8FKCO10020	10		6	20.5	18.5	19	19	10	34.5
8FKCO10030	10	G3/8	8	24	18.5	22	19	10	35.5
8FKCO12030	12		8	24	18.5	22	22	10	35.5

平行管螺纹阳接头



型号	适用管外径 øA	T	øB	øC	对边宽 E	L1	L2	L3
8FKHB08020	8	G1/4	5	20.5	19	10	10	21
8FKHB10020	10		6	20.5	19	10	10	22
8FKHB10030	10	G3/8	6	24	22	10	11	22
8FKHB12030	12		8	24	22	10	11.5	22.5

弯管接头





型号	适用管外径 øA	T	øB1	øB2	øC	D	对边宽		L1	L2	L3	L4
							E	F				
8FKMB06010	6	G1/8	4	4	17	17.5	17	14	8	13	14	33.5
8FKMB08020	8	G1/4	6	7	20.5	17.5	22	17	12	16	17	35.5
8FKMB10020	10		8	7	20.5	18.5	22	19	12	16	17	36.5
8FKMB12030	12	G3/8	10	9	24	18.5	27	22	12	19	22	40.5

阶式密封圈 (备件)



橡胶材质以NBR为标准规格、金属环以SPCC (冷轧钢板) 为标准规格。

阶式密封圈附带在接头处, 也作为备件单件销售。



型号	适用螺纹	ød	øD	t
8FKP-C-010	G1/8	9.9	17	2
8FKP-C-020	G1/4	13.3	20.5	2
8FKP-C-030	G3/8	16.8	24	2

● 安装接头的法兰面的密封请使用密封垫圈。(O形圈样式的G螺纹接头不能使用)

● 接头的套筒请使用日本伊原科技股份有限公司的套筒 (KKO)。